

Dynabrade Product Spotlight

DynaBrite Interleaf Wheels & Surface Conditioning Wheels



For Use on Dynisher Finishing Tools (Models 13400, 13450, 51585)
 Countless Applications on Stainless Steel, Composites and More



DynaBrite Interleaf Wheels

- Ideal for light deburring and cleaning of irregular parts and inside pipe diameters.
- Also for removing scale and various marks made by previous operations.



				ALUMINUM OXIDE COATED ABRASIVES					
Wheel Diameter	Wheel Width	Wheel Attachment	Maximum RPM	60 Grit Coarse	80 Grit Medium	120 Grit Medium	150 Grit Fine	240 Grit Very Fine	Package Quantity
4"	4"	3/4" Arbor Hole	5,000	79470	79471	79472	79473	79474	1
4-1/4"	2"	5/8"-11	5,000	79476	79477	79478	79479	79480	1
4-1/4"	4"	5/8"-11	5,000	79482	79483	79484	79485	79486	1

See Reverse Side for Additional Abrasive Wheels!

DynaBrite Interleaf Wheels & Surface Conditioning Wheels



For Use on Dynisher Finishing Tools (Models 13400, 13450, 51585)

DynaBrite Surface Conditioning Wheels

- Non-woven nylon wheels are ideal for imparting hairline finishes on stainless steel and aluminum.
- Also utilized for removal of handling marks.



SURFACE CONDITIONING (NON-WOVEN NYLON)

Wheel Diameter	Wheel Width	Wheel Attachment	Maximum RPM	Coarse	Medium	Fine	Very Fine	S-Ultra Fine	Package Quantity
4"	4"	3/4" Arbor Hole	5,000	79404	79405	79406	79407	79490	1
4-1/4"	2"	5/8"-11	5,000	79493	79494	79400	79401	79489	1
4-1/4"	4"	5/8"-11	5,000	79491	79492	79402	79403	79487	1

DynaBrite Felt Polishing Wheels

- For achieving mirror and sanitary finishes on stainless steel.



Wheel Diameter	Wheel Width	Wheel Attachment	Maximum RPM	Part Number	Package Quantity
4"	2"	3/4" Arbor Hole	5,000	79481	1
4"	4"	3/4" Arbor Hole	5,000	79475	1
4-1/4"	2"	5/8"-11	5,000	79488	1

DynaCut Aluminum Oxide Flap Wheels with Flanges

- The most common mineral for general purpose applications. Wheels are used for finishing flat, concave and convex surfaces.
- Also ideal for grinding internal and outer surfaces of tanks, containers and pipes. More applications include finishing parts and irregular shapes, such as handles, taps and molded parts; also used for removing and cleaning weld seams.



ALUMINUM OXIDE COATED ABRASIVES

Wheel Diameter	Wheel Thickness	Center Hole	Maximum RPM	40 Grit	60 Grit	80 Grit	120 Grit	Package Quantity
4"	4"	3/4"	6,800	90850	90847	90851	90852	1



For More Tools and Related Accessories, Visit: Dynabrade.com



DYNABRADE, INC.
8989 Sheridan Drive
Clarence, New York 14031-1419
Phone: 716-631-0100
US Fax: 716-631-2073
International Fax: 716-631-2524

US Consumers Call
Toll-Free: 1-800-828-7333

Canadian Consumers Call
Toll-Free: 1-800-344-1488



©DYNABRADE, INC., 2014
PRINTED IN USA

DYNABRADE EUROPE S.à r.l.
Zone Artisanale Op Tomm 6
L-5485 Wormeldange-Haut, Luxembourg
Phone: +352 768 494 1
Fax: +352 768 495

DYNABRADE INDIA ABRASIVE POWER TOOLS Pvt Ltd.

EL-54, TTC Industrial Area
M.I.D.C. Mahape
Electronic Zone
Navi Mumbai - 400705
Maharashtra, India
Phone: +91 22 2763 2226
Fax: +91 22 2763 2228



US Consumer Toll-Free Number: 1-888-DYNABRADE

DISTRIBUTED BY:

